

The following are guidelines you MUST follow when using a cardlock facility.

NO SMOKING - GASOLINE IS FLAMMABLE

Smoking is not permitted. Doing so could result in a serious fire and/or injury.

FIRE EXTINGUISHER LOCATION & USE

Location and instructions for use must be conspicuously posted.

TO USE:

- 1. Hold the extinguisher upright
- 2. Pull ring pin
- 3. Stand back 8 feet from the fire
- 4. Aim at base of fire and squeeze lever
- 5. Sweep side to side

IDENTIFY EMERGENCY EQUIPMENT

Emergency equipment has been installed at this site. Signs have been posted to help you identify it. **BEFORE** fueling, please note the location of the following emergency equipment.

- FIRE EXTINGUISHERS
- A RED EMERGENCY STOP BUTTON is on the card reader station panel. This will shut down the fuel pumps.
- AN EMERGENCY SHUT OFF SWITCH. This allows you to shut down the entire system from a location other than the fueling island. It is clearly identified with a sign. If a fire starts use the EFSO.
- A TELEPHONE or a fire alarm transmitting device.
- THE SITE OPERATOR'S telephone number is posted at the site. If you need assistance or need to report a spill or problem, call this number.

CONTAINERS

Only approved containers may be filled. Approved containers must be:

- 1. CLEARLY MARKED with the name of the liquid. (NFPA No. 30A, Sec. 9.2.3.2).
- 2. Constructed of metal or approved plastic, have a tight closure, and be fitted with a spout or be so designed that the contents can be poured without spilling. (OFC 3404.3 –NFPA 30 4.2).
- 3. A metal or plastic* safety that holds 5 gallons or less (NFPA 30 table 6.2.3).
- 4. A metal drum, meeting DOT specifications that holds 60 gallons or less (NFPA 30, Sec 4.2.3).

* An approved plastic container is one that has been tested and listed to be in compliance with the requirements of ASTM F 852 or F 976, ANSI/UL 1313, or 49 CFR.

PROCEDURES FOR FUELING PORTABLE CONTAINERS:

- 1. Portable containers up to 12 gallons must be placed on the ground before filling. DO NOT FILL PORTABLE CONTAINERS WHILE THEY ARE IN A TRUNK, A BOAT, OR BED OF A PICKUP! (NFPA No. 30A, Sec. 9.2.3.3)
- 2. Do not use latch open devices when filling portable containers.

OTHER PRECAUTIONS

• **STOP YOUR ENGINE** and put your vehicle in PARK or set your emergency brake. You **MUST STOP** your engine before fueling. Discharge static electricity before touching the nozzle.



• You must remain outside your vehicle and must attend the nozzle and be in full view of the nozzle while refueling.

HOW TO BEGIN FUELING

- Insert access card into the card reader and remove it. Directions will appear on the screen of the card reader.
- Enter your security number. Press ENTER. (On a two-card system, you will now enter the vehicle card using the same process).
- Enter your 5-digit odometer number or any other number. Press ENTER.
- Activate the pump by entering the pump number. Press ENTER.
- Lift the nozzle from the pump and insert the nozzle deeply into the fuel tank.
- Activate the pump by lifting the lever on the side of the pump.
- Pull the trigger on the nozzle and begin to dispense fuel.

The optimum nozzle setting for speed of delivery is between ½ and ¾ open. Faster delivery may result in a spill.

If the nozzle is activated too quickly, a leak detector will automatically slow pumping to a trickle. If this happens, release the trigger on the nozzle and wait 10 seconds. Pull trigger back on and pumping should be normal.

FUELING COMPLETED

- The nozzle should click off when the tank is full.
- Do not top off the tank (OAR 340-244-0232).
- Shut the pump off by moving the lever on the pump down.
- Return the nozzle to its hanger.

IN CASE OF FIRE, SPILL OR RELEASE

- 1. USE EMERGENCY PUMP SHUTOFF
- 2. CALL 911 TO REPORT THE ACCIDENT,

or press the fire alarm if no phone is available.

IN CASE OF SPILL OR RELEASE: CALL THE OPERATOR EMERGENCY NUMBER.

WARNING: Driving away with the nozzle still in your vehicle can result in fire or spill, which could lead to extreme damage and serious injury.

If you drive off with the nozzle in the vehicle, follow the procedures below:

- 1. STOP VEHICLE.
- 2. TURN PUMP OFF.
- 3. PUT HOSE BACK ON PUMP IF POSSIBLE.
- 4. REPORT INCIDENT USING EMERGENCY NUMBER POSTED AT SITE.

Advise of:

- Your Location
- Pump Number



- Date and Time
- Your Name and Telephone Number

If other assistance is needed call the emergency number and report the problem.

CAUTION! HAZARDOUS MATERIALS

ALL FUELS ARE HAZARDOUS. Read the following warning statements.

DANGERS OF GASOLINE

- Gasoline is extremely flammable.
- Harmful or fatal if swallowed.
- May be harmful if inhaled or absorbed through the skin.
- May cause irritation.
- Long term exposure to vapors has caused cancer in laboratory animals.
- Keep away from heat, sparks, and flame.
- Avoid breathing vapor.
- Use only in well ventilated locations.
- Avoid contact with eyes and prolonged contact with skin. Wash thoroughly after handling.
- Keep container closed.
- FOR USE AS MOTOR FUEL ONLY.

DANGERS OF DIESEL

- Diesel is combustible.
- May cause irritation to eyes.
- Avoid contact with eyes.
- Middle distillates (including diesel) have caused skin cancer and kidney damage in laboratory animals.
- Keep away from heat and flame.
- Use only in well ventilated locations.
- Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.
- Keep head away from container when opening or dispensing.

FIRST AID PROCEDURES

It is important that you follow these emergency and first aid procedures if you come into contact with gasoline and diesel fuel.

EYES: Flush with water for 15 minutes.

SKIN: Wash exposed areas with soap and water.

INGESTION: DO NOT induce vomiting. May cause chemical pneumonitis. Call doctor.



INHALATION: Should symptoms noted under physiological effects occur, remove to fresh air. If not breathing, apply artificial respiration.

OTHER INSTRUCTIONS: Remove gasoline or diesel-soaked clothing.

PHYSIOLOGICAL EFFECTS

Acute Effects - Severe with Short Duration

Gasoline AND Diesel:

- Causes slight to moderate eye irritation.
- Moderately irritating to the skin; causes redness, edema, or drying of the skin.

Gasoline:

- May cause dizziness; irritation of eyes, nose and throat; vomiting; and bluish color of the skin.
- To the central nervous system, may cause contracted pupils, loss of reflexes, convulsions, seizures, sudden loss of consciousness, coma, and sudden death.
- Other symptoms are: Headaches, mental confusion and depression, flushing of the face, loss of appetite, nausea, slurred speech, and difficulty in swallowing.

Diesel:

• Inhaling high concentrations of diesel vapors may cause drowsiness or unconsciousness (narcosis).

Chronic Effects - Severe with Long Duration

Recent studies with laboratory animals have shown that diesel and gasoline vapors cause kidney cancer in mice.

IMPORTANT NOTICE

This **FIRE SAFETY TRAINING BROCHURE** meets all requirements of Oregon Administrative Rules, Chapter 837, Division 20 and the Flammable Liquids Dispensing Regulations, ORS 480.345.

Please read and provide this information to all employees who are authorized to dispense fuel prior to dispensing. This brochure contains important information for those who operate nonretail fuel dispensing equipment.

RETURN the tear-off portion, signed and dated with the account number, to your cardlock operator to show compliance with Oregon laws.

FIRE SAFETY TRAINING RECEIPT

I certify that I have received and read the fire safety training material provided to me. I have also distributed the material to all employees under my supervision and certify that they have been trained in the safe operation of gasoline dispensing equipment at unattended automated fueling sites.

CUSTOMER NAME (please print)

CUSTOMER SIGNATURE

ACCOUNT NUMBER

DATE