

MATERIAL SAFETY DATA SHEET

EQUILON MSDS: 60500E-08 01/04/99

SHELL PELLA OIL A

TELEPHONE NUMBER:

24 HOUR EMERGENCY ASSISTANCE
ASSISTANCE

GENERAL MSDS

EQUIVA SERVICES: 877-276-7283

877-276-7285

CHEMTREC: 800-424-9300

NAME AND ADDRESS

EQUILON ENTERPRISES LLC

PRODUCT STEWARDSHIP

P.O. BOX 674414

HOUSTON, TX 77267-4414

SECTION I

NAME

PRODUCT: SHELL PELLA OIL A

CHEM NAME: STRAIGHT RUN MIDDLE DISTILLATE

CHEM FAMILY: PETROLEUM HYDROCARBON, INDUSTRIAL OIL,
"MINERAL SEAL" OIL

SHELL CODE: 61900

HEALTH HAZARD: 2 FIRE HAZARD: 1 REACTIVITY: 0

SECTION II-A

PRODUCT/INGREDIENT

NO.	COMPOSITION	CAS NO.	PERCENT
---	-----	-----	-----
P	PELLA OIL A		
1	STRAIGHT RUN MIDDLE DISTILLATE	64741-44-2	100

NFPA HAZARD RATING: HEALTH 0 FIRE 1 REACTIVITY 0

SECTION II-B

ACUTE TOXICITY DATA

NO.	ACUTE ORAL LD50 LC50	ACUTE DERMAL LD50	ACUTE INHALATION
---	-----	-----	-----
P	NOT AVAILABLE		

SECTION III

HEALTH INFORMATION

THE HEALTH EFFECTS NOTED BELOW ARE CONSISTENT WITH REQUIREMENTS UNDER THE OSHA

HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

EYE CONTACT: BASED ON ESSENTIALLY SIMILAR PRODUCT TESTING LIQUID IS

PRACTICALLY NONIRRITATING TO THE EYES.

SKIN CONTACT: BASED ON ESSENTIALLY SIMILAR PRODUCT TESTING LIQUID IS PRESUMED

TO BE MODERATELY IRRITATING TO THE SKIN. PROLONGED OR REPEATED

LIQUID CONTACT CAN RESULT IN DEFATTING AND DRYING OF THE SKIN

WHICH MAY RESULT IN SEVERE IRRITATION AND DERMATITIS.

MAY CAUSE

MILD SKIN SENSITIZATION. RELEASE DURING HIGH PRESSURE USAGE MAY

RESULT IN INJECTION OF OIL INTO THE SKIN CAUSING LOCAL NECROSIS.

INHALATION: INHALATION OF VAPORS OR MIST MAY CAUSE MILD IRRITATION TO THE

UPPER RESPIRATORY TRACT. HIGH CONCENTRATIONS MAY RESULT IN

CENTRAL NERVOUS SYSTEM DEPRESSION. INHALATION OF HIGH LEVELS OF

MIST MAY RESULT IN CHEMICAL PNEUMONITIS.

INGESTION: INGESTION OF PRODUCT MAY RESULT IN VOMITING; ASPIRATION

(BREATHING) OF VOMITUS INTO THE LUNGS MUST BE AVOIDED AS EVEN

SMALL QUANTITIES MAY RESULT IN ASPIRATION PNEUMONITIS.

SIGNS AND SYMPTOMS: IRRITATION AS NOTED ABOVE. SKIN SENSITIZATION (ALLERGY)

MAY BE EVIDENCED BY RASHES, ESPECIALLY HIVES. EARLY TO

MODERATE CNS (CENTRAL NERVOUS SYSTEM) DEPRESSION MAY BE

EVIDENCED BY GIDDINESS, HEADACHE, DIZZINESS AND NAUSEA; IN

EXTREME CASES, UNCONSCIOUSNESS AND DEATH MAY OCCUR. LOCAL

TISSUE NECROSIS IS EVIDENCED BY DELAYED ONSET OF PAIN AND

DAMAGE A FEW HOURS FOLLOWING INJECTION. ASPIRATION PNEUMONITIS MAY BE EVIDENCED BY COUGHING, LABORED

BREATHING AND CYANOSIS (BLUISH SKIN); IN SEVERE CASES DEATH MAY OCCUR.

AGGRAVATED MEDICAL CONDITIONS:

PREEXISTING SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. PREEXISTING SKIN OR LUNG ALLERGIES MAY INCREASE THE CHANCE OF DEVELOPING INCREASED ALLERGY SYMPTOMS FROM EXPOSURE TO THIS PRODUCT.

OTHER HEALTH EFFECTS:

KIDNEY DAMAGE MAY RESULT FOLLOWING ASPIRATION PNEUMONITIS. THE RESULTS OF ANIMAL BIOASSAYS ON MIDDLE DISTILLATE FUELS SHOW THAT PROLONGED DERMAL CONTACT PRODUCES A WEAK TO MODERATE CARCINOGENIC ACTIVITY. SEE SECTION VI FOR ADDITIONAL HEALTH INFORMATION.

SECTION IV

OCCUPATIONAL EXPOSURE LIMITS

COMP NO.	OSHA PEL/TWA	OSHA PEL/CEILING	ACGIH TLV/TWA	ACGIH TLV/STEL	OTHER
P	5 MG/M3*	NONE	5 MG/M3*	10 MG/M3*	

* OIL MIST, MINERAL - RECOMMENDED

SECTION V

EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: FLUSH EYES WITH WATER. IF IRRITATION OCCURS, GET MEDICAL

ATTENTION.

SKIN CONTACT: REMOVE CONTAMINATED CLOTHING/SHOES AND WIPE EXCESS FROM SKIN.

FLUSH SKIN WITH WATER. FOLLOW BY WASHING WITH SOAP AND WATER.

IF IRRITATION OCCURS, GET MEDICAL ATTENTION. DO NOT REUSE CLOTHING UNTIL CLEANED. IF MATERIAL IS INJECTED UNDER THE SKIN,

GET MEDICAL ATTENTION PROMPTLY TO PREVENT SERIOUS DAMAGE; DO NOT

WAIT FOR SYMPTOMS TO DEVELOP.

INHALATION: REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS

DIFFICULT. GET MEDICAL ATTENTION.
INGESTION: DO NOT INDUCE VOMITING. IF VOMITING OCCURS
SPONTANEOUSLY, KEEP
HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE
LUNGS.
GET MEDICAL ATTENTION.
NOTE TO PHYSICIAN: IF MORE THAN 2.0 ML PER KG HAS BEEN INGESTED
AND VOMITING
HAS NOT OCCURRED, EMESIS SHOULD BE INDUCED WITH
SUPERVISION. KEEP VICTIM'S HEAD BELOW HIPS TO PREVENT
ASPIRATION. IF SYMPTOMS SUCH AS LOSS OF GAG REFLEX,
CONVULSIONS OR UNCONSCIOUSNESS OCCUR BEFORE EMESIS,
GASTRIC
LAVAGE USING A CUFFED ENDOTRACHEAL TUBE SHOULD BE
CONSIDERED.

SECTION VI

SUPPLEMENTAL HEALTH INFORMATION

REPEATED DERMAL APPLICATION OF HIGH LEVELS OF MIDDLE
DISTILLATE FUELS IN
EXPERIMENTAL ANIMALS HAS PRODUCED EXTREMELY SEVERE
IRRITATION TO CORROSIVE
ACTION ON THE SKIN. VARYING DEGREES OF LIVER AND KIDNEY
DAMAGE WERE NOTED IN
THESE STUDIES, INCLUDING CONGESTION, ENLARGEMENT, MOTTLING,
AND MULTIFOCAL
NECROSIS.
MIDDLE DISTILLATE FUELS HAVE BEEN DEMONSTRATED TO CAUSE
CHROMOSOME DAMAGE IN
THE IN VIVO RAT BONE MARROW CYTOGENETICS ASSAY, AND
MUTAGENIC IN THE L5178Y
MOUSE LYMPHOMA ASSAY.

SECTION VII

PHYSICAL DATA

BOILING POINT (DEG F): SPECIFIC GRAVITY (H2O = 1): VAPOR PRESSURE
(MM HG):
475-610 0.8170 <0.1
MELTING POINT (DEG F): SOLUBILITY IN WATER: VAPOR DENSITY
(AIR = 1):
-35 (POUR POINT) NEGLIGIBLE >1
3.2-5.8

(CS @ 104 DEG F)

EVAPORATION RATE (NORMAL BUTYL ACETATE = 1):NOT AVAILABLE
APPEARANCE AND ODOR:CLEAR LIQUID; STRONG HYDROCARBON ODOR.
PHYS/CHEM PROPERTIES: SEE ABOVE FOR DETAILS

SECTION VIII

FIRE AND EXPLOSION HAZARDS

FLASH POINT AND METHOD: 225 DEG F (PMCC)

FLAMMABLE LIMITS/PERCENT VOLUME IN AIR: LOWER: 0.7 HIGHER: 6.0

EXTINGUISHING MEDIA:

USE WATER FOG, FOAM, DRY CHEMICAL OR CO2. DO NOT USE A DIRECT STREAM OF

WATER. PRODUCT WILL FLOAT AND CAN BE REIGNITED ON SURFACE OF WATER.

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS:

CAUTION. DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR (HELMET

WITH FACE SHIELD, BUNKER COATS, GLOVES AND RUBBER BOOTS), INCLUDING A

POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL

FIRE EXPOSED CONTAINERS WITH WATER. IN THE CASE OF LARGE FIRES, ALSO COOL

SURROUNDING EQUIPMENT AND STRUCTURES WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRES SHOULD BE COOLED WITH WATER TO

PREVENT VAPOR PRESSURE BUILDUP WHICH COULD RESULT IN CONTAINER RUPTURE.

CONTAINER AREAS EXPOSED TO DIRECT FLAME CONTACT SHOULD BE COOLED WITH LARGE

QUANTITIES OF WATER AS NEEDED TO PREVENT WEAKENING OF CONTAINER STRUCTURE.

SECTION IX

REACTIVITY

STABILITY: STABLE HAZARDOUS POLYMERIZATION WILL NOT OCCUR
CONDITIONS AND MATERIALS TO AVOID:

AVOID HEAT, FLAME AND CONTACT WITH STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS:

THERMAL DECOMPOSITION PRODUCTS ARE HIGHLY DEPENDENT ON THE COMBUSTION

CONDITIONS. A COMPLEX MIXTURE OF AIRBORNE SOLID, LIQUID, PARTICULATES AND GASES WILL EVOLVE WHEN THIS MATERIAL UNDERGOES PYROLYSIS OR COMBUSTION.

CARBON MONOXIDE AND OTHER UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED UPON COMBUSTION.

SECTION X

EMPLOYEE PROTECTION

RESPIRATORY PROTECTION:

USE A NIOSH-APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVEREXPOSURE. IN

ACCORD WITH 29 CFR 1910.134, USE EITHER A FULL-FACE, ATMOSPHERE-SUPPLYING

RESPIRATOR OR AN AIR-PURIFYING RESPIRATOR FOR ORGANIC VAPORS. PROTECTIVE CLOTHING

NO SPECIAL EYE PROTECTION IS ROUTINELY NECESSARY. AVOID PROLONGED OR

REPEATED CONTACT WITH SKIN. WEAR CHEMICAL RESISTANT GLOVES AND OTHER

CLOTHING AS REQUIRED TO MINIMIZE CONTACT.

ADDITIONAL PROTECTIVE MEASURES:

USE EXPLOSION-PROOF VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS.

SECTION XI

ENVIRONMENTAL PROTECTION

SPILL OR LEAK PROCEDURES:

CAUTION. *** LARGE SPILLS *** ELIMINATE POTENTIAL SOURCES OF IGNITION. WEAR

APPROPRIATE RESPIRATOR AND OTHER PROTECTIVE CLOTHING. SHUT OFF SOURCE OF

LEAK ONLY IF SAFE TO DO SO. DIKE AND CONTAIN. REMOVE WITH VACUUM TRUCKS OR

PUMP TO STORAGE/SALVAGE VESSELS. SOAK UP RESIDUE WITH AN ABSORBENT SUCH AS

CLAY, SAND, OR OTHER SUITABLE MATERIAL; PLACE IN NON-LEAKING CONTAINERS AND

SEAL TIGHTLY FOR PROPER DISPOSAL. FLUSH AREA WITH WATER TO REMOVE TRACE

RESIDUE; DISPOSE OF FLUSH SOLUTION AS ABOVE. *** SMALL SPILLS ***
TAKE UP
WITH AN ABSORBENT MATERIAL AND PLACE IN NON-LEAKING
CONTAINERS FOR PROPER
DISPOSAL.

SECTION XII

SPECIAL PRECAUTIONS

KEEP LIQUID AND VAPOR AWAY FROM HEAT, SPARKS AND FLAME.
SURFACES THAT ARE
SUFFICIENTLY HOT MAY IGNITE EVEN LIQUID PRODUCT IN THE ABSENCE
OF SPARKS OR
FLAME. EXTINGUISH PILOT LIGHTS, CIGARETTES AND TURN OFF OTHER
SOURCES OF
IGNITION PRIOR TO USE AND UNTIL ALL VAPORS ARE GONE. VAPORS
MAY ACCUMULATE AND
TRAVEL TO IGNITION SOURCES DISTANT FROM THE HANDLING SITE;
FLASH-FIRE CAN
RESULT. KEEP CONTAINERS CLOSED WHEN NOT IN USE. USE (ONLY) WITH
ADEQUATE
VENTILATION. CONTAINERS, EVEN THOSE THAT HAVE BEEN EMPTIED,
CAN CONTAIN
EXPLOSIVE VAPORS. DO NOT CUT, DRILL, GRIND, WELD OR PERFORM
SIMILAR OPERATIONS
ON OR NEAR CONTAINERS. WASH WITH SOAP AND WATER BEFORE
EATING, DRINKING,
SMOKING OR USING TOILET FACILITIES. LAUNDER CONTAMINATED
CLOTHING BEFORE REUSE.

SECTION XIII

TRANSPORTATION REQUIREMENTS

DEPARTMENT OF TRANSPORTATION CLASSIFICATION:
NOT HAZARDOUS BY D.O.T. REGULATIONS
DOT PROPER SHIPPING NAME: NOT APPLICABLE
OTHER REQUIREMENTS: NOT APPLICABLE

SECTION XIV

OTHER REGULATORY CONTROLS

THIS PRODUCT IS LISTED ON THE EPA/TSCA INVENTORY OF CHEMICAL
SUBSTANCES.

PROTECTION OF STRATOSPHERIC OZONE (PURSUANT TO SECTION 611 OF THE CLEAN AIR ACT AMENDMENTS OF 1990): PER 40 CFR PART 82, THIS PRODUCT DOES NOT CONTAIN NOR WAS IT DIRECTLY MANUFACTURED WITH ANY CLASS I OR CLASS II OZONE DEPLETING SUBSTANCES. IN ACCORDANCE WITH SARA TITLE III, SECTION 313, THE ATTACHED ENVIRONMENTAL DATA SHEET (EDS) SHOULD ALWAYS BE COPIED AND SENT WITH THE MSDS.

SECTION XV

STATE REGULATORY INFORMATION

THE FOLLOWING CHEMICALS ARE SPECIFICALLY LISTED BY INDIVIDUAL STATES; OTHER PRODUCT SPECIFIC HEALTH AND SAFETY DATA IN OTHER SECTIONS OF THE MSDS MAY ALSO BE APPLICABLE FOR STATE REQUIREMENTS. FOR DETAILS ON YOUR REGULATORY REQUIREMENTS YOU SHOULD CONTACT THE APPROPRIATE AGENCY IN YOUR STATE.

STATE LISTED COMPONENT	CAS NO	PERCENT	STATE CODE
------------------------	--------	---------	------------

STRAIGHT RUN MIDDLE DISTILLATE	64741-44-2	100	NJ
--------------------------------	------------	-----	----

CA = CALIFORNIA HAZ. SUBST. LIST; CA65 = CALIFORNIA SAFE DRINKING WATER AND TOXICS ENFORCEMENT ACT LIST; CT = CONNECTICUT TOX. SUBST. LIST; FL = FLORIDA SUBST. LIST; IL = ILLINOIS TOX. SUBST. LIST; LA = LOUISIANA HAZ. SUBST. LIST; MA = MASSACHUSETTS SUBST. LIST; ME = MAINE HAZ SUBST. LIST; MN = MINNESOTA HAZ. SUBST. LIST; NJ = NEW JERSEY HAZ. SUBST. LIST; PA = PENNSYLVANIA HAZ. SUBST. LIST; RI = RHODE ISLAND HAZ. SUBST. LIST.

SECTION XVI

SPECIAL NOTES

PRODUCT REFORMULATED. MSDS SECTIONS II-B, III, IV, VI, VIII, XV HAVE BEEN

REVISED TO REFLECT NEW INGREDIENT, PHYSICAL PROPERTIES, AND HEALTH HAZARD EVALUATION. THE EDS HAS BEEN REVISED IN SECTIONS I AND II.

THE INFORMATION CONTAINED IN THIS DATA SHEET IS BASED ON THE DATA AVAILABLE TO US AT THIS TIME, AND IS BELIEVED TO BE ACCURATE BASED UPON THAT DATA. IT IS PROVIDED INDEPENDENTLY OF ANY SALE OF THE PRODUCT, FOR PURPOSE OF HAZARD COMMUNICATION. IT IS NOT INTENDED TO CONSTITUTE PRODUCT PERFORMANCE INFORMATION, AND NO EXPRESS OR IMPLIED WARRANTY OF ANY KIND IS MADE WITH RESPECT TO THE PRODUCT, UNDERLYING DATA OR THE INFORMATION CONTAINED HEREIN. YOU ARE URGED TO OBTAIN DATA SHEETS FOR ALL PRODUCTS YOU BUY, PROCESS, USE OR DISTRIBUTE, AND ARE ENCOURAGED TO ADVISE THOSE WHO MAY COME IN CONTACT WITH SUCH PRODUCTS OF THE INFORMATION CONTAINED HEREIN.

TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT, YOU SHOULD CONSULT WITH YOUR LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENT AGENCY. WE WILL NOT PROVIDE ADVICE ON SUCH MATTERS, OR BE RESPONSIBLE FOR ANY INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN. THE UNDERLYING DATA, AND THE INFORMATION PROVIDED HEREIN AS A RESULT OF THAT DATA, IS THE PROPERTY OF EQUIVA SERVICES, LLC AND IS NOT TO BE THE SUBJECT OF SALE OR EXCHANGE WITHOUT THE EXPRESS WRITTEN CONSENT OF EQUIVA SERVICES, LLC.

ENVIRONMENTAL DATA SHEET
EQUILON EDS: 60500E
SHELL PELLA OIL A
TELEPHONE NUMBER:

24 HOUR EMERGENCY ASSISTANCE
ASSISTANCE

EQUIVA SERVICES: 877-276-7283

CHEMTREC: 800-424-9300

NAME AND ADDRESS

EQUILON ENTERPRISES

PRODUCT STEWARDSHIP

P.O. BOX 674414

HOUSTON, TX 77267-4414

PRODUCT CODE: 61900

GENERAL MSDS

877-276-7285

SECTION I PRODUCT COMPOSITION

NO.	COMPOSITION	CAS	PERCENT
=====			
=====			
P	PELLA OIL A		
1	STRAIGHT RUN MIDDLE DISTILLATE	64741-44-2	100

SECTION II SARA TITLE III INFORMATION

NO.	EHS RQ	EHS TPQ	SEC-313	313 CATEGORY	311/312 CATEGORY
	(*1)	(*2)	(*3)	(*4)	(*5)
=====					
=====					
P				H-1, H-2	

*1 = REPORTABLE QUANTITY OF EXTREMELY HAZARDOUS SUBSTANCE, SEC 302

*2 = THRESHOLD PLANNING QUANTITY, EXTREMELY HAZARDOUS SUBSTANCE, SEC 302

*3 = TOXIC CHEMICAL, SEC 313

*4 = CATEGORY AS REQUIRED BY SEC 313 (40 CFR 372.65 C), MUST BE USED ON TOXIC

RELEASE INVENTORY FORM

*5 = CATEGORY (FOR AGGREGATE REPORTING REQUIREMENTS UNDER SARA 311, 312)

HEALTH: H-1 = IMMEDIATE (ACUTE) HEALTH HAZARD

H-2 = DELAYED (CHRONIC) HEALTH HAZARD

PHYSICAL: P-3 = FIRE HAZARD

P-4 = SUDDEN RELEASE OF PRESSURE HAZARD

P-5 = REACTIVE HAZARD

SECTION III ENVIRONMENTAL RELEASE INFORMATION

THIS PRODUCT IS COVERED BY EPA'S COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION AND LIABILITY ACT (CERCLA) PETROLEUM EXCLUSION. THEREFORE RELEASES TO AIR, LAND, OR WATER ARE NOT REPORTABLE UNDER CERCLA ("SUPERFUND"). HOWEVER UNDER SECTION 311 OF EPA'S CLEAN WATER ACT (CWA), THIS PRODUCT IS CONSIDERED AN OIL. AS SUCH, SPILLS INTO OR LEADING TO SURFACE WATERS THAT CAUSE A SHEEN MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER, 800-424-8802. THIS PRODUCT IS AN OIL UNDER 49 CFR (DOT) PART 130. IF SHIPPED BY RAIL OR HIGHWAY IN A TANK WITH A CAPACITY OF 3,500 GALLONS OR MORE, IT IS SUBJECT TO THE REQUIREMENTS OF PART 130. MIXTURE SOLUTIONS IN WHICH THIS PRODUCT IS PRESENT AT 10% OR MORE MAY ALSO BE SUBJECT TO THIS RULE.

SECTION IV RCRA INFORMATION

IF THIS PRODUCT BECOMES A WASTE, IT WOULD NOT BE A HAZARDOUS WASTE BY RCRA CRITERIA (40 CFR 261). PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH LOCAL REGULATIONS.

THE INFORMATION CONTAINED IN THIS DATA SHEET IS BASED ON THE DATA AVAILABLE TO US AT THIS TIME, AND IS BELIEVED TO BE ACCURATE BASED UPON THAT DATA. IT IS PROVIDED INDEPENDENTLY OF ANY SALE OF THE PRODUCT, FOR PURPOSE OF HAZARD COMMUNICATION. IT IS NOT INTENDED TO CONSTITUTE PRODUCT PERFORMANCE

INFORMATION, AND NO EXPRESS OR IMPLIED WARRANTY OF ANY KIND IS MADE WITH RESPECT TO THE PRODUCT, UNDERLYING DATA OR THE INFORMATION CONTAINED HEREIN. YOU ARE URGED TO OBTAIN DATA SHEETS FOR ALL PRODUCTS YOU BUY, PROCESS, USE OR DISTRIBUTE, AND ARE ENCOURAGED TO ADVISE THOSE WHO MAY COME IN CONTACT WITH SUCH PRODUCTS OF THE INFORMATION CONTAINED HEREIN.

TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT, YOU SHOULD CONSULT WITH YOUR LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENT AGENCY. WE WILL NOT PROVIDE ADVICE ON SUCH MATTERS, OR BE RESPONSIBLE FOR ANY INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN. THE UNDERLYING DATA, AND THE INFORMATION PROVIDED HEREIN AS A RESULT OF THAT DATA, IS THE PROPERTY OF EQUIVA SERVICES, LLC AND IS NOT TO BE THE SUBJECT OF SALE OR EXCHANGE WITHOUT THE EXPRESS WRITTEN CONSENT OF EQUIVA SERVICES, LLC.

KAREN G. HAYNES

EQUIVA SERVICES LLC
P.O. BOX 674414
HOUSTON, TX 77267-4414

FOR ADDITIONAL INFORMATION ON THIS ENVIRONMENTAL DATA PLEASE CALL

(877) 276-7285

FOR EMERGENCY ASSISTANCE PLEASE CALL

EQUIVA SERVICES LLC: (877) 276-7283

CHEMTREC: (800) 424-9300

}

