



SAFETY DATA SHEET

according to SS 586

SDS # : 081913

QUARTZ 9000 ENERGY 0W-40

Issuing date: 2015-07-16

Revision Date: 2015-09-11

Version 1.01

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name	QUARTZ 9000 ENERGY 0W-40
Number	BY3
Substance/mixture	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Motor oil.
------------------------	------------

1.3. Details of the supplier of the safety data sheet

Supplier	TOTAL OIL ASIA PACIFIC PTE LTD 331 North Bridge Road #23-01 Odeon Towers Singapore 188720 Tel: +65 6879 2200 Fax: +65 6879 2203
-----------------	--

For further information, please contact:

Contact Point	HSE
E-mail Address	ms.ap-sds@total.com

1.4. Emergency telephone number

Singapore: 800-101-2201 (toll-free in country) or +65 3158 1349
International: CHEMTREC +1 703 527 3887 (collect calls accepted)

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification
Serious eye damage/eye irritation - Category 2

Label elements



SAFETY DATA SHEET

according to SS 586

SDS # : 081913

QUARTZ 9000 ENERGY 0W-40

Issuing date: 2015-07-16

Revision Date: 2015-09-11

Version 1.01

Signal Word
WARNING

Precautionary Statements - Prevention

- Wash face, hands and any exposed skin thoroughly after handling
- Wear eye/face protection

Precautionary Statements - Response

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention

Other hazards which do not result in classification

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental properties Should not be released into the environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature The product is made from refined mineral base oils and synthetic oils

Chemical Name	CAS-No	EC-No	Weight %
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	68037-01-4	500-183-1	<50
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	93819-94-4	298-577-9	<1.5

4. FIRST AID MEASURES

4.1. Description of first-aid measures

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.



SAFETY DATA SHEET

according to SS 586

SDS # : 081913

QUARTZ 9000 ENERGY 0W-40

Issuing date: 2015-07-16

Revision Date: 2015-09-11

Version 1.01

Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.
Skin contact	Remove contaminated clothing and shoes. Wash off with soap and water. Wash contaminated clothing before reuse.
Inhalation	Move to fresh air.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact	Not classified.
Eye contact	Causes serious eye irritation.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media	Carbon dioxide (CO ₂). ABC powder. Foam. Water spray or fog.
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special Hazard	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.
-----------------------	--

5.3. Advice for fire-fighters

Special protective equipment for fire-fighters	Wear self-contained breathing apparatus and protective suit.
Other information	Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.



SAFETY DATA SHEET

according to SS 586

SDS # : 081913

QUARTZ 9000 ENERGY 0W-40

Issuing date: 2015-07-16

Revision Date: 2015-09-11

Version 1.01

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Personal Protective Equipment See Section 8 for more detail.

Waste treatment See section 13.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.

Prevention of fire and explosion Take precautionary measures against static discharges: Ground/bond containers, tanks and transfer/receiving equipment.

Hygiene measures Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

7.2. Conditions for safe storage, including any incompatibilities



SAFETY DATA SHEET

according to SS 586

SDS # : 081913

QUARTZ 9000 ENERGY 0W-40

Issuing date: 2015-07-16

Revision Date: 2015-09-11

Version 1.01

Technical measures/Storage conditions

Keep away from food, drink and animal feedingstuffs. Keep in a banded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.

Materials to Avoid

Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

Mineral oil mist:
USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined).

Legend

See section 16

8.2. Exposure controls

Occupational Exposure Controls
Engineering Measures

Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Personal Protective Equipment
General Information

If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). Type A/P2. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.

Eye Protection

If splashes are likely to occur, wear: Safety glasses with side-shields.

Skin and body protection

Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.



SAFETY DATA SHEET

according to SS 586

SDS # : 081913

QUARTZ 9000 ENERGY 0W-40

Issuing date: 2015-07-16

Revision Date: 2015-09-11

Version 1.01

Hand Protection

Hydrocarbon-proof gloves: Fluorinated rubber, Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves.

Environmental exposure controls

General Information

The product should not be allowed to enter drains, water courses or the soil.

9. PHYSICAL AND CHEMICAL PROPERTIES

General Information

Color	yellow
Physical State @20°C	liquid
Odor	Characteristic

Important health safety and environmental information

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH		No information available	
Boiling point/boiling range		No information available	
Flash point	> 200 °C > 392 °F		
Evaporation rate		No information available	
Flammability Limits in Air		No information available	
Vapor Pressure		No information available	
Vapor density		No information available	
Density	844 kg/m ³	@ 15 °C	
Water solubility		Insoluble	
Solubility in other solvents		No information available	
logPow		No information available	
Autoignition temperature		No information available	
Viscosity, kinematic	76.4 mm ² /s 13.5 mm ² /s	@ 40 °C @ 100 °C	ISO 3104 ISO 3104
Explosive properties	Not explosive		
Oxidizing Properties	No information available		
Possibility of hazardous reactions	No information available		



SAFETY DATA SHEET

according to SS 586

SDS # : 081913

QUARTZ 9000 ENERGY 0W-40

Issuing date: 2015-07-16

Revision Date: 2015-09-11

Version 1.01

Other information

No information available

10. STABILITY AND REACTIVITY

10.1. Reactivity

General Information No information available.

10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous Reactions None under normal processing.

10.4. Conditions to Avoid

Conditions to Avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.

10.5. Incompatible Materials

Materials to Avoid Strong oxidizing agents.

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity

Information on likely routes of exposure

Principle Routes of Exposure Inhalation, Skin contact, Eye contact, Ingestion.

Numerical measures of toxicity - Product Information

No information available



SAFETY DATA SHEET

according to SS 586

SDS # : 081913

QUARTZ 9000 ENERGY 0W-40

Issuing date: 2015-07-16

Revision Date: 2015-09-11

Version 1.01

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated 68037-01-4	LD50 > 5000 mg/kg (Rat)	LD50 > 2000 mg/kg (Rat)	LC50 (4h) > 5.2 mg/l (Rat)
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) 93819-94-4	LD50 2600 mg/kg (Rat)	LD50 > 3160 mg/kg (Rabbit - OECD 402)	

Information on toxicological effects

Skin contact	Not classified.
Eye contact	Causes serious eye irritation.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Not classified.
Serious eye damage/eye irritation	Irritating to eyes.
Sensitization	Not classified as a sensitizer. No known effect based on information supplied.
Germ Cell Mutagenicity	This product is not classified as mutagenic. No known effect based on information supplied.
Carcinogenicity	This product is not classified carcinogenic. No known effect based on information supplied.
Reproductive toxicity	Not classified. No known effect based on information supplied.
STOT-single exposure	Not classified. No known effect based on information supplied.
STOT - repeated exposure	Not classified. No known effect based on information supplied.
Aspiration Hazard	Not classified. No known effect based on information supplied.

12. ECOLOGICAL INFORMATION



SAFETY DATA SHEET

according to SS 586

SDS # : 081913

QUARTZ 9000 ENERGY 0W-40

Issuing date: 2015-07-16

Revision Date: 2015-09-11

Version 1.01

12.1. Toxicity

Not Classified.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated 68037-01-4	EL50 (72h) > 1000 mg/l (Scenedesmus capricornutum - OECD 201)	EC50 (48h) 190 mg/l (Daphnia magna) LE50(48h) > 1000 mg/l (Daphnia magna)	LC50(96h) > 750 mg/l (Pimephales promelas) LL50(96h) > 1000 mg/l (Pimephales promelas)	
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) 93819-94-4	EbC50 (96h) 2.1 mg/l Selenastrum capricornutum (OECD 201)	EL50 (48h) 5.4 mg/l Daphnia magna (OECD 202)	LC50 (96h) 4.5 mg/l Oncorhynchus mykiss (OECD 203)	

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated 68037-01-4	NOELR (72h) 1000 mg/l (Scenedesmus capricornutum - OECD 201)	NOELR (21d) 125 mg/l (Daphnia magna - OECD 211)		

Effects on terrestrial organisms

No information available.

12.2. Persistence and degradability

General Information No information available.

12.3. Bioaccumulative potential

Product Information No information available.

logPow No information available

Component Information .



SAFETY DATA SHEET

according to SS 586

SDS # : 081913

QUARTZ 9000 ENERGY 0W-40

Issuing date: 2015-07-16

Revision Date: 2015-09-11

Version 1.01

Chemical Name	log Pow
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) - 93819-94-4	0.9

12.4. Mobility in soil

Soil	Given its physical and chemical characteristics, the product generally shows low soil mobility.
Air	Loss by evaporation is limited.
Water	Insoluble. The product spreads on the surface of the water.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

12.6. Other adverse effects

General Information No information available.

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Methods	Should not be released into the environment. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. After use, this oil must be sent to a licensed waste oil facility. Incorrect disposal of used oil poses a risk to the environment. Mixture with other waste types such as solvents, brake- and cooling liquids is forbidden.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
Disposal Precautions	Refer to section 8 for safety and protective measures for disposal personnel.

14. TRANSPORT INFORMATION

<u>ADR/RID</u>	Not regulated
<u>IMDG/IMO</u>	Not regulated
<u>ICAO/IATA</u>	Not regulated

15. REGULATORY INFORMATION



SAFETY DATA SHEET

according to SS 586

SDS # : 081913

QUARTZ 9000 ENERGY 0W-40

Issuing date: 2015-07-16

Revision Date: 2015-09-11

Version 1.01

International Inventories No information available

National regulatory information

Singapore

Applicable National Regulation
Workplace Safety and Health (General Provision) Regulations

16. OTHER INFORMATION

Abbreviations, acronyms

Legend Section 8

TWA: Time Weight Average

STEL: Short Time Exposure Limit

+ Sensitizer

** Hazard Designation

M: Mutagen

*

Skin designation

C:

Carcinogen

R:

Toxic to reproduction

Revision Date: 2015-09-11

Revision Note *** Indicates updated section.

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the safety data sheet