



**SAFETY DATA SHEET**  
Valvoline™ ULTRA LOW VISCOSITY  
Transmission Fluid

Version: 3.7

Revision Date: 01/12/2026

Print Date:  
03/12/2026

---

**SECTION 1. IDENTIFICATION**

Product name : Valvoline™ ULTRA LOW VISCOSITY  
Transmission Fluid

Product code : 888460

**Manufacturer or supplier's details**

Company name of supplier : Valvoline Global Operations

Address : 100 Valvoline Way  
Lexington, KY 40509  
United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvolineglobal.com

Emergency telephone number : +1-800-VALVOLUME (+1-800-825-8654)

---

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Skin sensitisation : Category 1

**Other hazards**

None known.

**GHS label elements**

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**  
P261 Avoid breathing mist or vapours.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves.

**Response:**



**SAFETY DATA SHEET**  
Valvoline™ ULTRA LOW VISCOSITY  
Transmission Fluid

Version: 3.7

Revision Date: 01/12/2026

Print Date:  
03/12/2026

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/  
attention.  
P362 + P364 Take off contaminated clothing and wash it before  
reuse.

**Disposal:**

P501 Dispose of contents/ container to an approved waste  
disposal plant.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	CAS No./Unique ID	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7*	>= 45 - <= 70
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8*	>= 15 - <= 40
Mineral Oil - mixture	-	>= 3 - <= 7
Alkyl acetamide	-	>= 0.5 - <= 1.5
LONG CHAIN HYDROXYALKYLAMINE	-	>= 0.1 - <= 1
CALCIUM SULFONATE	-	>= 0.1 - <= 1
methyl-1H-benzotriazole	29385-43-1*	>= 0.1 - <= 1

\* Indicates that the identifier is a CAS No.

---

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical  
advice.  
If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water.

In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.



**SAFETY DATA SHEET**  
Valvoline™ ULTRA LOW VISCOSITY  
Transmission Fluid

Version: 3.7

Revision Date: 01/12/2026

Print Date:  
03/12/2026

---

If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	No symptoms known or expected. May cause an allergic skin reaction.
Notes to physician	:	No hazards which require special first aid measures. Treat symptomatically.

---

**SECTION 5. FIREFIGHTING MEASURES**

Unsuitable extinguishing media	:	High volume water jet
Hazardous combustion products	:	carbon dioxide and carbon monoxide
Further information	:	Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

---

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
---	---	---



**SAFETY DATA SHEET**  
 Valvoline™ ULTRA LOW VISCOSITY  
 Transmission Fluid

Version: 3.7

Revision Date: 01/12/2026

Print Date:  
03/12/2026

- Advice on safe handling : Do not breathe vapours/dust.  
 Avoid exposure - obtain special instructions before use.  
 Avoid contact with skin and eyes.  
 For personal protection see section 8.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Dispose of rinse water in accordance with local and national regulations.  
 Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
 Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

**Personal protective equipment**

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water



**SAFETY DATA SHEET**  
Valvoline™ ULTRA LOW VISCOSITY  
Transmission Fluid

Version: 3.7

Revision Date: 01/12/2026

Print Date:  
03/12/2026

---

Skin and body protection	:	Tightly fitting safety goggles Impervious clothing
Hygiene measures	:	Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wash hands before breaks and at the end of workday.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	liquid
Odour	:	No data available
Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	408 °F / 209 °C Method: Cleveland open cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.8377 g/ml
Solubility(ies)	:	
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-	:	No data available



**SAFETY DATA SHEET**  
Valvoline™ ULTRA LOW VISCOSITY  
Transmission Fluid

Version: 3.7

Revision Date: 01/12/2026

Print Date:  
03/12/2026

---

octanol/water  
Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : No data available

Viscosity, kinematic : 20.57 mm<sup>2</sup>/s (104 °F / 40 °C)

Oxidizing properties : No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.  
Chemical stability : No decomposition if stored and applied as directed.  
Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : excessive heat  
Heat  
No data available

Incompatible materials : Alkali metals  
aluminum  
Ammonia  
Combustible material  
halogens  
Lead  
Metals  
metal oxides  
Oxidizing agents  
peroxides  
reducing agents  
sodium  
Strong acids  
strong bases  
water  
Zinc  
Peroxides  
Not applicable

Hazardous decomposition products : No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**

Not classified due to lack of data.

**Components:**

**methyl-1H-benzotriazole:**



**SAFETY DATA SHEET**  
Valvoline™ ULTRA LOW VISCOSITY  
Transmission Fluid

Version: 3.7

Revision Date: 01/12/2026

Print Date:  
03/12/2026

Acute oral toxicity : LD50: > 300 - < 2,000 mg/kg  
Assessment: The component/mixture is moderately toxic after single ingestion.

**Skin corrosion/irritation**

Not classified due to lack of data.

**Product:**

Remarks : May cause skin irritation and/or dermatitis.

**Components:**

**Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:**

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials

**LONG CHAIN HYDROXYALKYLAMINE:**

Assessment : No skin irritation

**Serious eye damage/eye irritation**

Not classified due to lack of data.

**Product:**

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

**Components:**

**Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : The toxicological data has been taken from products of similar composition.

**LONG CHAIN HYDROXYALKYLAMINE:**

Result : Slight, transient irritation  
Assessment : Slight, transient irritation

**methyl-1H-benzotriazole:**

Result : Slight, transient irritation



**SAFETY DATA SHEET**  
Valvoline™ ULTRA LOW VISCOSITY  
Transmission Fluid

Version: 3.7

Revision Date: 01/12/2026

Print Date:  
03/12/2026

**Respiratory or skin sensitisation**

**Skin sensitisation**

May cause an allergic skin reaction.

**Respiratory sensitisation**

Not classified due to lack of data.

**Product:**

Remarks : Causes sensitisation.

**Components:**

**Alkyl acetamide:**

Result : The product is a skin sensitiser, sub-category 1B.

**LONG CHAIN HYDROXYALKYLAMINE:**

Assessment : The product is a skin sensitiser, sub-category 1B.

**CALCIUM SULFONATE:**

Assessment : May cause sensitisation by skin contact.

Remarks : The toxicological data has been taken from products of similar composition.

**methyl-1H-benzotriazole:**

Assessment : Does not cause skin sensitisation.

**Germ cell mutagenicity**

Not classified due to lack of data.

**Carcinogenicity**

Not classified due to lack of data.

**Components:**

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:**

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

**Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:**

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

**Mineral Oil - mixture:**

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)



**SAFETY DATA SHEET**  
Valvoline™ ULTRA LOW VISCOSITY  
Transmission Fluid

Version: 3.7

Revision Date: 01/12/2026

Print Date:  
03/12/2026

- IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
- NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified due to lack of data.

**Product:**

Reproductive toxicity - Assessment : No toxicity to reproduction

**Components:**

**methyl-1H-benzotriazole:**

Effects on fertility : Application Route: Oral  
Result: Some evidence of adverse effects on development, based on animal experiments.

Effects on foetal development : Application Route: Oral  
Result: Some evidence of adverse effects on development, based on animal experiments.

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

**STOT - single exposure**

Not classified due to lack of data.

**STOT - repeated exposure**

Not classified due to lack of data.

**Aspiration toxicity**

Not classified due to lack of data.

**Components:**

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:**

May be fatal if swallowed and enters airways.

**Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:**

May be fatal if swallowed and enters airways.

**Mineral Oil - mixture:**

May be fatal if swallowed and enters airways.



**SAFETY DATA SHEET**  
Valvoline™ ULTRA LOW VISCOSITY  
Transmission Fluid

Version: 3.7

Revision Date: 01/12/2026

Print Date:  
03/12/2026

**Further information**

**Product:**

Remarks : No data available

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Product:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**Components:**

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:**

Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
plants Exposure time: 72 h

Toxicity to fish (Chronic : NOEC (Fish): 10 mg/l  
toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l  
aquatic invertebrates  
(Chronic toxicity)

**Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**Mineral Oil - mixture:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.



**SAFETY DATA SHEET**  
Valvoline™ ULTRA LOW VISCOSITY  
Transmission Fluid

Version: 3.7

Revision Date: 01/12/2026

Print Date:  
03/12/2026

**Alkyl acetamide:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**LONG CHAIN HYDROXYALKYLAMINE:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Harmful to aquatic life.

Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Harmful to aquatic life with long lasting effects.

**CALCIUM SULFONATE:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): > 1,000 mg/l  
Exposure time: 96 h

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

**methyl-1H-benzotriazole:**

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): 55 mg/l  
Exposure time: 96 h  
Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 8.58 mg/l  
Exposure time: 48 h  
Test Type: static test  
Remarks: Information given is based on data on the components and the ecotoxicology of similar products.

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 62 mg/l  
Exposure time: 72 h



**SAFETY DATA SHEET**  
Valvoline™ ULTRA LOW VISCOSITY  
Transmission Fluid

Version: 3.7

Revision Date: 01/12/2026

Print Date:  
03/12/2026

**Ecotoxicology Assessment**

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**Persistence and degradability**

**Components:**

**CALCIUM SULFONATE:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 16 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

**Bioaccumulative potential**

**Components:**

**CALCIUM SULFONATE:**

Partition coefficient: n-octanol/water : log Pow: 10.88  
Remarks: Information taken from reference works and the literature.

**methyl-1H-benzotriazole:**

Partition coefficient: n-octanol/water : log Pow: 1.71

**Mobility in soil**

No data available

**Other adverse effects**

**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
Protection of Stratospheric Ozone - CAA Section 602 Class I  
Substances  
Remarks: This product neither contains, nor was  
manufactured with a Class I or Class II ODS as defined by the  
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +  
B).

Additional ecological information : No data available



**SAFETY DATA SHEET**  
Valvoline™ ULTRA LOW VISCOSITY  
Transmission Fluid

Version: 3.7

Revision Date: 01/12/2026

Print Date:  
03/12/2026

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

- Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

---

**SECTION 14. TRANSPORT INFORMATION**

**International Regulations**

**UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations**

**49 CFR**

Not regulated as a dangerous good

**Special precautions for user**

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

---

**SECTION 15. REGULATORY INFORMATION**

**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
benzene	71-43-2	10	10 (D018)
toluene	108-88-3	100	100 (F005)
methanol	67-56-1	100	100 (F003)
ethylbenzene	100-41-4	100	100 (F003)



**SAFETY DATA SHEET**  
Valvoline™ ULTRA LOW VISCOSITY  
Transmission Fluid

Version: 3.7

Revision Date: 01/12/2026

Print Date:  
03/12/2026

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Respiratory or skin sensitisation

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

**Clean Water Act**

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

benzene	71-43-2	>= 0 - < 0.1 %
formaldehyde	50-00-0	>= 0 - < 0.1 %
ethylbenzene	100-41-4	>= 0 - < 0.1 %
naphthalene	91-20-3	>= 0 - < 0.1 %
toluene	108-88-3	>= 0 - < 0.1 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

benzene	71-43-2	>= 0 - < 0.1 %
formaldehyde	50-00-0	>= 0 - < 0.1 %
ethylbenzene	100-41-4	>= 0 - < 0.1 %
naphthalene	91-20-3	>= 0 - < 0.1 %
toluene	108-88-3	>= 0 - < 0.1 %

**US State Regulations**

**Massachusetts Right To Know**

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8
Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified	64742-55-8
sulphur dioxide	7446-09-5



**SAFETY DATA SHEET**  
 Valvoline™ ULTRA LOW VISCOSITY  
 Transmission Fluid

Version: 3.7

Revision Date: 01/12/2026

Print Date:  
03/12/2026

trimethyl phosphate 512-56-1

**Pennsylvania Right To Know**

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified 64742-54-7  
 Distillates (petroleum), hydrotreated light paraffinic; Baseoil — unspecified 64742-55-8  
 PROPRIETARY OF 000000284639 Not Assigned  
 Mineral Oil - mixture Not Assigned

**Maine Chemicals of High Concern**

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified 64742-54-7  
 benzene 71-43-2  
 ethylbenzene 100-41-4  
 naphthalene 91-20-3  
 toluene 108-88-3

**Vermont Chemicals of High Concern**

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified 64742-54-7  
 benzene 71-43-2  
 formaldehyde 50-00-0  
 ethylbenzene 100-41-4  
 naphthalene 91-20-3  
 toluene 108-88-3

**Washington Chemicals of High Concern**

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified 64742-54-7  
 benzene 71-43-2  
 formaldehyde 50-00-0  
 ethylbenzene 100-41-4  
 naphthalene 91-20-3  
 toluene 108-88-3

**The components of this product are reported in the following inventories:**

- TCSI : On the inventory, or in compliance with the inventory
- TSCA : All substances listed as active on the TSCA inventory
- AIIC : On the inventory, or in compliance with the inventory
- CA. DSL : All components of this product are on the Canadian DSL
- ENCS : Not in compliance with the inventory
- KECI : Not in compliance with the inventory
- PICCS : Not in compliance with the inventory
- IECSC : Not in compliance with the inventory



**SAFETY DATA SHEET**  
 Valvoline™ ULTRA LOW VISCOSITY  
 Transmission Fluid

Version: 3.7

Revision Date: 01/12/2026

Print Date:  
03/12/2026

NZIoC : Not in compliance with the inventory

**TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.


**Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

**SECTION 16. OTHER INFORMATION**

**Further information**

**NFPA 704:**



**HMIS® IV:**

<b>HEALTH</b>	/	<b>2</b>
<b>FLAMMABILITY</b>		<b>1</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1  
Limits for Air Contaminants
- ACGIH / TWA : 8-hour, time-weighted average
- OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response,



**SAFETY DATA SHEET**  
Valvoline™ ULTRA LOW VISCOSITY  
Transmission Fluid

Version: 3.7

Revision Date: 01/12/2026

Print Date:  
03/12/2026

Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 01/12/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information : 000000275196