

SAFETY DATA SHEET



XPR SAE 0W-20

Section 1. Identification

GHS product identifier : XPR SAE 0W-20
Product code : 301073175115
Other means of identification : Not available.
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Lubricating Oil	
Uses advised against	Reason
None known.	

Supplier's details : Calumet Branded Products, LLC
1060 N Capitol Ave Suite 6-401
Indianapolis, IN 46204
USA
Technical Services:317-328-5660

Emergency telephone number : 24 hr. CHEMTREC 1-800-424-9300 / International 1-703-527-3887

Section 2. Hazards identification

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

Classification of the substance or mixture : Not classified.

GHS label elements

Signal word : No signal word.
Hazard statements : No known significant effects or critical hazards.

Precautionary statements

General : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention : Not applicable.
Response : Not applicable.
Storage : Not applicable.
Disposal : Not applicable.

Hazards not otherwise classified : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture
Other means of identification : Not available.

Ingredient name	%	CAS number
Dec-1-ene, homopolymer, hydrogenated	≥50 - ≤75	68037-01-4
Distillates (petroleum), hydrotreated heavy paraffinic	≤9	64742-54-7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≤9	64742-65-0
Distillates (petroleum), hydrotreated light paraffinic	≤9	64742-55-8
Distillates (petroleum), solvent-dewaxed light paraffinic	≤9	64742-56-9
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	≤3	72623-87-1
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts	≤1.6	84605-29-8
Distillates (petroleum), hydrotreated middle	≤1.4	64742-46-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Section 4. First aid measures

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : Do not use water jet.

Specific hazards arising from the chemical : In a fire or if heated, a pressure increase will occur and the container may burst.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
sulfur oxides
phosphorus oxides
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8).
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Dec-1-ene, homopolymer, hydrogenated Distillates (petroleum), hydrotreated heavy paraffinic	None. ACGIH TLV (United States, 1/2022). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 5/2018). [Oil mist, mineral] TWA: 5 mg/m ³ 8 hours. NIOSH REL (United States, 10/2020). [OIL MIST MINERAL] TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ACGIH TLV (United States, 1/2022). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 5/2018). [Oil mist, mineral] TWA: 5 mg/m ³ 8 hours. NIOSH REL (United States, 10/2020). [OIL MIST MINERAL] TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist
Distillates (petroleum), hydrotreated light paraffinic	ACGIH TLV (United States, 1/2022). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 5/2018). [Oil mist, mineral] TWA: 5 mg/m ³ 8 hours. NIOSH REL (United States, 10/2020). [OIL MIST MINERAL] TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist
Distillates (petroleum), solvent-dewaxed light paraffinic	ACGIH TLV (United States, 1/2022).

Section 8. Exposure controls/personal protection

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts

Distillates (petroleum), hydrotreated middle

[Mineral Oil, pure, highly and severely refined]

TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction

OSHA PEL (United States, 5/2018). [Oil mist, mineral]

TWA: 5 mg/m³ 8 hours.

NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]

TWA: 5 mg/m³ 10 hours. Form: Mist

STEL: 10 mg/m³ 15 minutes. Form: Mist

NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]

TWA: 5 mg/m³ 10 hours. Form: Mist

STEL: 10 mg/m³ 15 minutes. Form: Mist

None.

NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]

TWA: 5 mg/m³ 10 hours. Form: Mist

STEL: 10 mg/m³ 15 minutes. Form: Mist

ACGIH TLV (United States).

As total hydrocarbon vapor: 200 mg/m³ 8 hours.

Biological exposure indices

No exposure indices known.

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 8. Exposure controls/personal protection

- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

- Physical state** : Liquid.
Color : Purple.
Odor : Not available.
Odor threshold : Not available.
pH : Not available.
Melting point/freezing point : Not available.
Boiling point, initial boiling point, and boiling range : Not available.
Flash point : Open cup: 225.56°C (438°F) [Cleveland]
Evaporation rate : Not available.
Flammability : Not available.
Lower and upper explosion limit/flammability limit : Not available.
Vapor pressure :

Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Distillates (petroleum), hydrotreated heavy paraffinic	<0.08	<0.011	ASTM D 5191			

- Relative vapor density** : Not available.

- Relative density** : 0.8501

Media	Result
cold water	Not soluble
hot water	Not soluble

- Solubility in water** : Not available.

- Partition coefficient: n-octanol/water** : Not applicable.

Ingredient name	°C	°F	Method
Distillates (petroleum), hydrotreated middle	225	437	

- Decomposition temperature** : Not available.

- Viscosity** : Kinematic (40°C (104°F)): 37.55 mm²/s (37.55 cSt)

- Flow time (ISO 2431)** : Not available.

- Pour point** : -64°C (-83.2°F)

Particle characteristics

- Median particle size** : Not applicable.

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : No specific data.
- Incompatible materials** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Dec-1-ene, homopolymer, hydrogenated	LC50 Inhalation Dusts and mists	Rat	>5.2 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum), hydrotreated heavy paraffinic	LC50 Inhalation Dusts and mists	Rat	5.7 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LC50 Inhalation Dusts and mists	Rat	>5.53 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum), hydrotreated light paraffinic	LC50 Inhalation Dusts and mists	Rat	>5.53 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum), solvent-dewaxed light paraffinic	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	2.18 mg/l	4 hours
Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr) esters, zinc salts	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat - Male, Female	>2.3 mg/l	4 hours
Distillates (petroleum), hydrotreated middle	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	3.2 g/kg	-
	LC50 Inhalation Dusts and mists	Rat - Male, Female	>5266 mg/m ³	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-

Irritation/Corrosion

Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr) esters, zinc salts	Eyes - Severe irritant	Rabbit	-	-	-
	Skin - Irritant	Rat	-	-	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Name	Result
Dec-1-ene, homopolymer, hydrogenated	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated light paraffinic	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed light paraffinic	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated middle	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Section 11. Toxicological information

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
XPR SAE 0W-20	287708.2	2618.7	N/A	N/A	134.9
Dec-1-ene, homopolymer, hydrogenated	N/A	2500	N/A	N/A	N/A
Distillates (petroleum), hydrotreated heavy paraffinic	N/A	2500	N/A	N/A	5.7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	N/A	2500	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light paraffinic	N/A	2500	N/A	N/A	N/A
Distillates (petroleum), solvent-dewaxed light paraffinic	N/A	2500	N/A	N/A	N/A
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	N/A	2500	N/A	N/A	N/A
Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr) esters, zinc salts	3200	2500	N/A	N/A	1.5
Distillates (petroleum), hydrotreated middle	N/A	2500	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotreated heavy paraffinic	Acute EC50 >100 mg/l	Daphnia	48 hours
	Acute IC50 >100 mg/l	Algae	72 hours
	Acute LC50 >100 mg/l	Fish	96 hours
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Acute EC50 >100 mg/l	Algae	72 hours
	Acute EC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
Distillates (petroleum), hydrotreated light paraffinic	Chronic NOEL >1 mg/l	Daphnia	21 days
	Acute EC50 >100 mg/l	Algae	72 hours
	Acute EC50 >100 mg/l	Daphnia	48 hours
Distillates (petroleum), solvent-dewaxed light paraffinic	Acute LC50 >100 mg/l	Fish	96 hours
	Acute LC50 4.5 mg/l	Fish	96 hours
	Acute EC50 >100 mg/l	Algae	72 hours
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	Acute EC50 >100 mg/l	Crustaceans	48 hours

Section 12. Ecological information

Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr) esters, zinc salts	Acute LC50 >100 mg/l Acute LC50 10 to 100 mg/l	Fish Fish	96 hours 96 hours
Distillates (petroleum), hydrotreated middle	Acute NOEC 1.8 mg/l Chronic NOEC <1 mg/l Acute EC50 2 to 100 mg/l	Fish Daphnia Algae	4 days 21 days 72 hours
	Acute EC50 2 to 100 mg/l Acute LC50 2 to 100 mg/l	Crustaceans Fish	48 hours 96 hours

Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr) esters, zinc salts	-	1.5 % - Not readily - 28 days	-	-
	OECD 301B Ready Biodegradability - CO ₂ Evolution Test	1.5 % - 28 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Distillates (petroleum), hydrotreated heavy paraffinic	-	-	Not readily
Distillates (petroleum), hydrotreated light paraffinic	-	-	Inherent
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	-	-	Inherent
Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr) esters, zinc salts	-	-	Not readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Dec-1-ene, homopolymer, hydrogenated	>6.5	-	High
Distillates (petroleum), hydrotreated heavy paraffinic	>6	-	High
Distillates (petroleum), solvent-dewaxed heavy paraffinic	2 to 6	-	High
Distillates (petroleum), hydrotreated light paraffinic	>6	-	High
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	>6	-	High
Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr) esters, zinc salts	0.56	-	Low

Mobility in soil

Section 12. Ecological information

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

U.S. Federal regulations : **TSCA 8(a) PAIR:** naphthalene
TSCA 8(a) CDR Exempt/Partial exemption: Not determined
Clean Water Act (CWA) 307: Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts; zinc O,O',O'-tetrakis(1,3-dimethylbutyl) bis (phosphorodithioate)

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Not listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Section 15. Regulatory information

Classification : Not applicable.

Composition/information on ingredients

Name	%	Classification
Dec-1-ene, homopolymer, hydrogenated	≥50 - ≤75	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated light paraffinic	≤9	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed light paraffinic	≤9	ASPIRATION HAZARD - Category 1
Phosphorodithioic acid, mixed O, O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts	≤1.6	ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1
Distillates (petroleum), hydrotreated middle	≤1.4	FLAMMABLE LIQUIDS - Category 4 ASPIRATION HAZARD - Category 1

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr) esters, zinc salts	84605-29-8	≤1.6
Supplier notification	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr) esters, zinc salts	84605-29-8	≤1.6

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

- Massachusetts** : None of the components are listed.
New York : None of the components are listed.
New Jersey : The following components are listed: ZINC compounds
Pennsylvania : The following components are listed: ZINC COMPOUNDS

California Prop. 65

This product is not known to contain California Prop 65 substances ≥1 ppm

International lists

National inventory

- Australia** : All components are listed or exempted.
Canada : All components are listed or exempted.
China : At least one component is not listed.
Eurasian Economic Union : **Russian Federation inventory**: Not determined.
New Zealand : All components are listed or exempted.
Philippines : All components are listed or exempted.
Republic of Korea : All components are listed or exempted.
Taiwan : All components are listed or exempted.
Thailand : Not determined.
Turkey : Not determined.
United States : All components are active or exempted.
Viet Nam : Not determined.

Section 16. Other information

National Fire Protection Association (U.S.A.)



Section 16. Other information

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Classification	Justification
Not classified.	

History

Date of issue/Date of revision : 09/12/2024

Date of previous issue : 05/21/2024

Version : 7.01

Key to abbreviations

: ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 N/A = Not available
 SGG = Segregation Group
 UN = United Nations

☑ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.