

# SAFETY DATA SHEET



**Date Issued :** 03/25/2005  
**SDS No :** 10025  
**Date Revised :** 03/29/2021  
**Revision No :** 20

## ACETONE

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** ACETONE

**ALTERNATE TRADE NAME(S):** 2-Propanone, ACS GRADE, SEMI GRADE, Technical Grade

**MANUFACTURER**

Tarr, LLC  
 P.O. Box 12570  
 Portland, OR 97212  
**Customer Service:** 503-288-5294

**24 HR. EMERGENCY TELEPHONE NUMBERS**

**CHEMTREC (US Transportation) :**(800) 424 - 9300

### 2. HAZARDS IDENTIFICATION

**GHS CLASSIFICATIONS**

Target Organ Toxicity (Single exposure), Category 3

**Health:**

Eye Irritation, Category 2

**Physical:**

Flammable Liquids, Category 2

**GHS LABEL**



Flame



Exclamation  
mark

**SIGNAL WORD:** DANGER

**HAZARD STATEMENTS**

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

**PRECAUTIONARY STATEMENTS**

**General:**

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P270: Do not eat, drink or smoke when using this product.

**Prevention:**

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

**ACETONE**

P240: Ground and bond container and receiving equipment.

**Response:**

P314: Get medical advice/attention if you feel unwell.

**Storage:**

P102: Keep out of reach of children.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

**EMERGENCY OVERVIEW**

**IMMEDIATE CONCERNS:** DANGER! Highly flammable liquid and vapor. Harmful or fatal if swallowed. Vapor harmful. May cause central nervous system depression. May be irritating to eyes, skin, nose, throat and respiratory tract.

**POTENTIAL HEALTH EFFECTS**

**EYES:** Liquid is severely irritating to the eyes. High vapor concentrations are also irritating.

**SKIN:** Liquid is mildly irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**INGESTION:** Ingestion may cause headache, dizziness, fatigue, and central nervous system depression.

**INHALATION:** Vapors may be irritating to the nose, throat, and respiratory tract. Exposure to high vapor concentrations may cause central nervous system (CNS) depression.

**MEDICAL CONDITIONS AGGRAVATED:** Pre-existing eye and skin disorders may be aggravated by exposure.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Chemical Name	Vol. %	CAS
Acetone	> 99	67-64-1

**4. FIRST AID MEASURES**

**EYES:** Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

**SKIN:** Flush skin with water while removing contaminated clothing. If irritation occurs, get medical attention. Do not reuse clothing or shoes until cleaned.

**INGESTION:** Do not give liquids if victim is unconscious or drowsy. Otherwise, give 2 glasses of water and induce vomiting by giving 30cc syrup of ipecac (or touching finger to the back of victim's throat). Keep victim's head below hips while vomiting. Call doctor.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

**ACUTE EFFECTS:** Irritation as noted above. Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur. Aspiration pneumonitis may be evidenced by coughing, labored breathing and cyanosis (bluish skin). Liver damage may be evidenced by loss of appetite, jaundice and sometimes pain in the upper abdomen on the right side.

**NOTES TO PHYSICIAN:** If victim is a child, give no more than 1 glass of water and 15cc (1 tablespoon) syrup of ipecac. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before emesis, gastric lavage should be considered following intubation with a cuffed endotracheal tube.

**5. FIRE FIGHTING MEASURES**

**ACETONE**

**FLAMMABLE CLASS:** Class IB flammable liquid.

**GENERAL HAZARD:** Flammable Liquid and Vapor! Contact with strong oxidizers may cause fire.

**EXTINGUISHING MEDIA:** Use water fog, "alcohol" foam, dry chemical, or CO<sub>2</sub>.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon monoxide and unidentified organic compounds may be formed during combustion.

**EXPLOSION HAZARDS:** When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

**FIRE FIGHTING PROCEDURES:** WARNING! Flammable Liquid. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

**6. ACCIDENTAL RELEASE MEASURES****ENVIRONMENTAL PRECAUTIONS**

**WATER SPILL:** Keep material out of storm sewers and ditches which lead to waterways.

**GENERAL PROCEDURES:** WARNING. Flammable. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Only specially trained or qualified personnel should handle the emergency.

**7. HANDLING AND STORAGE**

**GENERAL PROCEDURES:** Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

**COMMENTS:** KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death. Observe all federal, state, and local regulations and National Fire Protection Association (NFPA) Codes with pertain to the specific local conditions of stage and use, including OSHA 29 CFR 1910.106 and NFPA 30, 70, 77, and 497.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
EXPOSURE LIMITS				
Chemical Name	Type		ppm	mg/m <sup>3</sup>
Acetone	OSHA PEL	TWA	1000	2400
	ACGIH TLV	TWA	500	
		STEL	750	

**ENGINEERING CONTROLS:** Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

**PERSONAL PROTECTIVE EQUIPMENT**

**ACETONE**

**EYES AND FACE:** Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

**SKIN:** Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**RESPIRATORY:** If exposure may or does exceed occupational exposure limits (Sec. 8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

**WORK HYGIENIC PRACTICES:** Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

**OTHER USE PRECAUTIONS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**COMMENTS:** May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name	Flash Point (°C)	Boiling Point (°C)	Freezing Point (°C)	Solubility in Water	Specific Gravity
Acetone	-17.2	56.111	-95.556	Miscible	0.797

**PHYSICAL STATE:** Liquid

**ODOR:** Pungent odor.

**APPEARANCE:** Clear

**COLOR:** Water-white.

**pH:** NA = Not Applicable

**PERCENT VOLATILE:** 100

**FLASH POINT AND METHOD:** ~ -26°C (-15°F) IP 170

**FLAMMABLE LIMITS:** 2.6 %Vol to 12.8 %Vol

**AUTOIGNITION TEMPERATURE:** No data available.

**VAPOR PRESSURE:** 24.7 kPa at 20 deg C/68 deg F (ASTM D-4052)

**VAPOR DENSITY:** ~ 2 20 deg C/68 deg F (air = 1)

**BOILING POINT:** 56°C (133°F)

**SOLUBILITY IN WATER:** Complete.

**EVAPORATION RATE:** 5.6 (ASTM D3539, nBuAc=1)

**DENSITY:** 6.62 at (60°F)

**SPECIFIC GRAVITY:** 0.79 to 0.81 15.5°C/60°F

**(VOC):** EPA granted acetone exempt-VOC status

## 10. STABILITY AND REACTIVITY

**REACTIVITY:** Yes

**HAZARDOUS POLYMERIZATION:** Avoid heat, flame, and other sources of ignition.

**ACETONE**

**STABILITY:** Stable under ordinary conditions of use and storage.

**CONDITIONS TO AVOID:** Avoid heat, sparks, flame and contact with strong oxidizing agents. Prevent vapor accumulation.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide and unidentified organic compounds may be formed during combustion. There should be no decomposition if stored and applied as directed.

**INCOMPATIBLE MATERIALS:** Strong oxidizers.

**11. TOXICOLOGICAL INFORMATION****ACUTE TOXICITY**

Chemical Name	ORAL LD <sub>50</sub>
Acetone	5800 mg/kg (Rat)

**NOTES:** Material may cause eye irritation. Direct contact with the liquid or exposure to its vapors or mists may cause stinging, tearing, redness, swelling and eye damage.

**GENERAL COMMENTS:** None identified.

**12. ECOLOGICAL INFORMATION**

**ENVIRONMENTAL DATA:** Readily biodegradable.

**ECOTOXICOLOGICAL INFORMATION:** Keep out of waterways.

**BIOACCUMULATION/ACCUMULATION:** Not expected to bioaccumulate significantly.

**13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

**EMPTY CONTAINER: KEEP OUT OF REACH OF CHILDREN!** Empty containers retain product residue and can be dangerous. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

**RCRA/EPA WASTE INFORMATION:** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

**14. TRANSPORT INFORMATION****DOT (DEPARTMENT OF TRANSPORTATION)**

**PROPER SHIPPING NAME:** Acetone

**PRIMARY HAZARD CLASS/DIVISION:** 3

**UN/NA NUMBER:** 1090

**PACKING GROUP:** II

**NAERG:** 128

**REPORTABLE QUANTITY (RQ) UNDER CERCLA:** 5,000 pounds

**ACETONE****LABEL:** Flammable liquid**MARINE POLLUTANT #1:** No**15. REGULATORY INFORMATION****UNITED STATES****DOT LABEL SYMBOL AND HAZARD CLASSIFICATION**

Flammable  
Liquid

S23: Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

**SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

**311/312 HEALTH HAZARDS:** This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

**313 REPORTABLE INGREDIENTS:** To the best of our knowledge, this product is not listed as a toxic chemical under Section 313 of SARA Title III.

**302/304 EMERGENCY PLANNING**

**EMERGENCY PLAN:** To the best of our knowledge, this product is not listed as an extremely hazardous substance.

**CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)**

Chemical Name	Vol. %	CERCLA RQ
Acetone	> 99	5,000 LBS.

**CERCLA RQ:** 5,000 lbs. RQ is for Acetone

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

Chemical Name	CAS
Acetone	67-64-1

**CALIFORNIA PROPOSITION 65:** To the best of our knowledge this material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

**CANADA****WHMIS HAZARD SYMBOL AND CLASSIFICATION**

Flammable  
Liquid

S15: Keep away from heat.

**GENERAL COMMENTS:** The regulatory information is not intended to be comprehensive. Other regulations may

**ACETONE**

apply to this material.

## 16. OTHER INFORMATION

**REASON FOR ISSUE:** Reviewed and issued a new revision date.


**PREPARED BY:** Compliance    **Date Revised:** 03/29/2021

**REVISION SUMMARY:** This SDS replaces the 03/26/2018 SDS. Revised: **Section 1:** SDS No.

### HMIS RATING

<b>HEALTH</b>		<b>1</b>
<b>FLAMMABILITY</b>		<b>3</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>
<b>PERSONAL PROTECTION</b>		<b>G</b>

### NFPA CODES



**NFPA STORAGE CLASSIFICATION:** These ratings are part of a specific hazard communication program and should be disregarded where individuals are not trained in the use of this hazard rating system. You should be familiar with the hazard communication programs applicable to your workplace.

**HMIS RATINGS NOTES:** The HMIS rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in the SDS must be considered.

**MANUFACTURER DISCLAIMER:** The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.